

Power-Solv

Section 1 Identification

Trade Name: Product Identification: Synonyms: Power-Solv 4205 Trichloroethylene

Product Use Description: Solvent Cleaner General Info Phone: (800) 795-9222 Emergency Phone: (800) 535-5053

Manufactured By: ABC Compounding Co., Inc. PO Box 16247 Atlanta, GA 30321

Apple Products

Section 2 Hazards Identification

Classifications

Carcinogenicity - Category 1B Germ Cell Mutagenicity - Category 2 Sensitization - Skin - Category 1B Skin Irritation - Category 2 Eye Irritation - Category 2 Specific Target Organ Toxicity (single exposure) - Category 3 Gasses under pressure - Compressed gas



Signal Word: Danger

Hazard Statements

Keep out of reach of children.

Read label and SDS before use.

Contains gas under pressure; may explode if heated.

May cause cancer; suspected of causing genetic defects (route of exposure: inhalation)

May cause drowsiness or dizziness.

Causes skin irritation

May cause an allergic skin reaction.

Causes serious eye irritation.

Precautionary Statements

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Pressurized container: Do not pierce or burn, even after use.

Wash hands and face thoroughly after handling.

Wear protective gloves, clothing, and eye protection.

Do not eat, drink or smoke when using this product.

Contaminated clothing must not be allowed out of the workplace.

Response

Trade Name:Power-SolvSDS #:4205Page 1 of 6SDS ID:SDS02879Revision # 1Revision Date09/23/2015



Power-Solv

IF SWALLOWED: Immediately call a poison center or a doctor. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs get medical attention.

Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center or doctor if you feel unwell.

If EXPOSED or CONCERNED: Get medical attention.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up.

Disposal

Dispose of contents and container in accordance with all local, regional, and national regulations.

Hazards Not Otherwise Specified

Not applicable

| Section 3 Composition | | | |
|-----------------------|--------------|--------------------|--|
| | | Concentration | |
| Chemical Name | <u>CAS #</u> | <u>% by Weight</u> | |
| Trichloroethylene | 79-01-6 | >=95 <= 100 | |
| Carbon Dioxide | 124-38-9 | >=1 <= 5 | |

Section 4 First Aid

EMERGENCY OVERVIEW

DANGER. Contents under pressure. Harmful or fatal if swallowed. Vapor harmful. Keep away from heat and flame. Can cause nervous system depression.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical attention.

SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs get medical attention. Take off contaminated clothing and wash it before reuse.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

INGESTION: May be harmful or fatal if swallowed. Seek medical attention immediately.

Section 5 Fire Fighting Measures

| Trade Name: | Power-Solv | SDS #: | 4205 | | Page 2 of 6 |
|-------------|------------|------------|------|---------------|-------------|
| SDS ID: | SDS02879 | Revision # | 1 | Revision Date | 09/23/2015 |



Power-Solv

Suitable fire extinguishing media:

Use water spray, fog or foam.

Specific hazards arising from the chemical:

In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous thermal decomposition products:

Hydrogen Chloride, Carbon Dioxide, Carbon Monoxide

Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6 Accidental Release Measures

Personal precautions:

Put on appropriate personal protective equipment (see section 8)

Environmental precautions and clean-up methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Section 7 Handling and Storage

Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120 F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

Section 8 Exposure Controls/Personal Protection

Trichloroethylene OSHA PEL

100 ppm

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: When respiratory protection is required use an organic vapor cartridge. A respiratory program that

meets OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements must be followed.

Engineering Controls: Good general ventilation required.

| Trade Name: | Power-Solv | |
|-------------|------------|--|
| SDS ID: | SDS02879 | |



Power-Solv

Section 9 Physical and Chemical Properties

Value

Property Appearance Boiling Point Decomposition Temperature Explosive Limit Ranges Flash Point Odor Other Information Partition Coeff Relative Density Vapor Density Viscosity

CLEAR SPRAY/MIST NOT AVAILABLE NOT AVAILABLE NONE SOLVENT VOC content (wt. %): 98 NOT AVAILABLE 1.45 4.5 (air=1) NOT AVAILABLE

Auto Ignition Temp Color Evaporation Rate Explosive Properties Melting/Freezing Point Odor Threshold Oxidizing Properties Physical State Solubility (Water) Vapor Pressure pH NOT AVAILABLE COLORLESS 6.4 (Butyl Acetate=1) NOT AVAILABLE NOT AVAILABLE NOT AVAILABLE LIQUID INSOLUBLE 60 mm Hg @20 C NOT APPLICABLE

Section 10 Stability and Reactivity

Reactivity :Under normal conditions of storage and use, hazardous reactions will not occur.Chemical Stability :Stable under normal conditions.Incompatible Materials :Alkalis, strong oxidizers, chemically active metals (aluminum, lithium, magnesium)Conditions to Avoid :High temperatures, open flames, sparks, welding.Decomposition Products:Hydrogen chloride, CO, CO2

Section 11 Toxicological Information

Primary Route of Entry: Skin contact, inhalation

Acute/Potential Health Effects:

EYES: May cause serious eye irritation. Symptoms include stinging, tearing and redness.

SKIN: May cause skin irritation. Prolonged or repeated contact may dry the skin and cause sensitization. Symptoms may

include redness, burning, drying of skin and skin burns.

INHALATION: High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause

headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. May

cause peripheral nervous system disorder and/or damage.

INGESTION: Harmful or fatal if swallowed.

Chronic / Long Term Effects: Possible cancer hazard. Damage to liver and other organs has been observed in workers who have been overexposed.

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous

system damage. Signs and Symptoms of Overexposure: Signs and symptoms of overexposure to this material through

breathing, swallowing, and/or passage of material through the skin may include: stomach or intestinal upset (nausea vomiting,

diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue,

nausea, headache, unconsciousness).

Target Organ Effects: Central nervous system, skin, liver.

Reproductive/Developmental Information: Human mutation data has been reported for Trichloroethylene.

Carcinogenic Information: Trichloroethylene: NIOSH - occupational carcinogen; OSHA: possible Select carcinogen; IARC: Group

2A carcinogen. WARNING: This product contains chemicals known to the State of California to cause cancer.

Acute Toxicity Values:

| Trade Name: | Power-Solv | SDS #: | 4205 | | Page 4 of 6 |
|-------------|------------|------------|------|---------------|-------------|
| SDS ID: | SDS02879 | Revision # | 1 | Revision Date | 09/23/2015 |



Power-Solv

Trichloroethylene: Inhalation - LC50, 4 hr, mouse 8450 ppm; Oral - LD50, mouse 2402 mg/Kg.

Section 12 Ecological Information

Trichloroethylene: LC50, Fathead minnow, 96 hr, 40.7 mg/l

Section 13 Disposal Considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

Section 14 Transport Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may

not reflect those exceptions and may not apply to all shipping modes or package sizes.

| UN number | 1950 | | |
|----------------------|------|-------------------|-------|
| Proper shipping name | | Aerosols, nonflam | mable |
| Class | 2.2 | | |
| Packing group | | - | |

Section 15 Regulatory Information

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act)

Trichloroethylene

CERCLA RQ (40 CFR 302) Trichloroethylene

100 lbs

Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (40 CFR 372.65) Trichloroethylene

If identified components of this product are CERCLA hazardous substances and/or listed under Sections 302, 304, or 313 of

Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning

and Community Right-To-Know Act), or under <u>California Proposition 65</u> (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire (X) Pressure (X) Reactive () Not Applicable ()

T.S.C.A. Status: All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

<u>RCRA Status</u>: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)

U228, F001 or D040

| 0228,100101004 | ·0 | | | | |
|----------------|------------|------------|------|---------------|-------------|
| Trade Name: | Power-Solv | SDS #: | 4205 | | Page 5 of 6 |
| SDS ID: | SDS02879 | Revision # | 1 | Revision Date | 09/23/2015 |
| | | | | | |



Power-Solv

Section 16 Other Information

HMIS Ratings :

| HEALTH | 2 |
|---------------------|---|
| FLAMMABILITY | 1 |
| REACTIVITY | 0 |
| PERSONAL PROTECTION | G |

Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

Preparation/Revision Date: 9/23/15

| Trade Name: | Power-Solv | SDS #: | 4205 | | Page 6 of 6 |
|-------------|------------|------------|------|---------------|-------------|
| SDS ID: | SDS02879 | Revision # | 1 | Revision Date | 09/23/2015 |