

Floor Care
with a
PEEL

E145

RESILIENT FLOOR CARE

Allure Floor Finish

This metal-crosslinked, modified acrylic floor finish provides excellent lay down gloss and superior response to high speed burnishing. It can be maintained with either conventional low-speed programs or infrequent (2-3 times a week) high speed burnishing.

Directions

- 1) Thoroughly strip floor with a stripper.
- 2) Rinse floor thoroughly with clean water.
- 3) Apply a sealer base (optional) to worn floors or high traffic floors to improve wear-resistance and enhance gloss.
- 4) Apply 2-4 coats of floor finish in uniform thin coats allowing time to dry thoroughly between coats. Allow for longer drying time in damp weather.

Maintenance

Sweep as necessary. Damp mop or scrub lightly with a mild, neutral detergent. Spray buff or buff lightly with appropriate pad. Also excellent for high-speed buffing. In high traffic areas, recoat worn spots as necessary.

Safety Cautions

Keep out of reach of children. It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation.

Refer to S.D.S. for additional safety information.



CLASSIFIED BY
UNDERWRITERS LABORATORIES INC.®
AS TO SLIP RESISTANCE ONLY.
2M05

Core Facts

Excellent gloss

Superior response to high speed burnishing

Good Durability

Typical Properties

Specific Gravity: 1.02

Solid Content: 18%

pH: 8.3

Leveling: Excellent

Film Formation: Excellent

Gloss: Excellent

Water resistance: Excellent

Detergent resistance: Very Good - Excellent

Removability: Excellent

Black heal mark resistance: Very Good

Slip Resistance: 0.6 (James Static Coefficient of Friction)

Odor: Slight Ammonia

Appearance: White Emulsion

Distributed by:
Apple Products Inc.
P. O. Box 16247 Atlanta, GA 30321
www.applechemicals.net



TM
086893TECHPE-111815